The State Board of Health Primary and Secondary School Regulations Washington Administrative Code 246-366-040, requires Spokane Regional Health District (SRHD) to complete a plan review of proposed changes or modifications to any portion of a school playground. The following list of materials must be submitted for plan review to the SRHD School Health & Safety Program (SH&S). It is recommended that proposed equipment cutsheets be submitted for review prior to ordering the equipment.

The Environmental Health Specialist responsible for your school will review the submitted materials. A site visit may be required as part of the review process. After plan review is completed and the equipment has been installed, a final pre-occupancy inspection will be required prior to commissioning the playground. The fee for plan review, site visits and pre-occupancy inspections will be billed at the hourly rate listed in SRHD's fee schedule. Contact SH&S at 324-1560, ext. 4 for further information.

The Playground Plan Review Packet includes:

- Playground Plan Review Submittal Instructions (this sheet)
- Playground Plan Review Information Form
- Playground Plan Review Example School Playground Layout Plan

To initiate the plan review process, please submit the following information:

- 1. Complete the following *Playground Plan Review Information Form*.
- 2. An overhead drawing or footprint plan showing the proposed playground equipment layout with the following information (refer to Example School Playground Layout Plan):
 - Show the containment border for all surfacing material under the playground equipment.
 - Show the location of fences, trees, buildings, concrete, asphalt, and septic system drain fields.
 - Provide a directional arrow to show true north.
 - Show the locations of all existing playground equipment.
 - Show all the equipment to be installed. Note activities that will be attached to composite (multi-activity) structures.
 - Show the use zone around each piece of equipment. Show the distances between each piece of equipment (existing and new) and from equipment to the containment border using arrows. If drawn to scale, indicate scale on drawing.
 - Show the distance of the slide use exit zone from the end of the slide and also the length of the flat exit region at the end of the slide bed (11 inches long minimum length, 0 to -4 degree slope). The slide exit use zone is equal to the height of the slide and measured out from the end of the slide bed, but may not be less than 6 feet and does not need to be greater than 8 feet.
 - Show the heights of all decks or platforms for each piece of equipment. Indicate whether platforms have guardrails or barriers.
 - Show the heights of all balance beams, spring toys, seesaws or other equipment less than 30 inches in height. The maximum allowable height for balance beams is 12 inches for 2 to 5 year year-olds and 16 inches for 5 to 12 year olds.
 - Show the heights of all upper body equipment (arch climbers, overhead ladders, etc.). The maximum allowable height is 84 inches for 5 to 12 year olds and 60 inches for 2 to 5 year olds.
 - Show the handle height for track rides. The allowable handle height is 64 to 78 inches.
 - Show the heights of all swing structures. To-and-fro swings are measured from the ground to pivot point; tire swings are measured from the seat to pivot point.

- 3. Cut sheets from the manufacturer with a picture of each new piece of equipment including design specifications.
- 4. A letter from the manufacturer or representative stating that the specific equipment being purchased meets or exceeds the standards in the current American Society for Testing and Materials Standard Consumer Safety Performance Specification for Playground Equipment for Public Use (ASTM *F 1487-17*) and U.S. Consumer Product Safety Commission (CPSC) Public Playground Safety Handbook (November 2010).
- 5. If equipment pieces are located closer than the minimum use zones specified in the CPSC and ASTM standards, provide a letter from the manufacturer stating the equipment is designed to be installed in this configuration (i.e. 'functionally linked').

Mailing address:

Spokane Regional Health District Environmental Public Health Division 1101 W. College Ave., Ste. 402 Spokane, WA 99201-2095

Phone number: 324.1560, ext. 4



SCHOOL HEALTH & SAFETY PROGRAM


K-12 School Playground Project Submittal

Project Information						
Project Type	☐ New equipment ☐ Relocating equipment ☐ Other:					
Site Information	School Name:					
	School Address:					
mormation	School District:					
School Contact Information	School Project Manager:					
	Address:					
	Office Phone:	Cell Phone:				
	Email:					
	Person to receive billing/invoices:					
Billing Information	Mailing Address:					
	Office Phone:		Cell Phone:			
	Email:					
Equipment Manufacturer/	Manufacturer representative:					
	Installer Company:					
Installer	Installer representative:					
Contact Information	Office Phone:		Cell Phone:			
information	Email:					
Estimated start date:			Estimated completion date:			
Surfacing Infor	mation					
What type of surfaces will be installed?		unitary synthetic materials* engineered wood fiber* pea gravel sand wood chips shredded tires shredded bark *ADA accessible surfacing materials				
How deep will the materials be?		inches				
	mer Product Safety Co about surfacing mater		ound Safety Handbook (November 2010) section 2.4 pages 8-			
Site Design Info	ormation					
What is the intended user age group for the playground?			2–5 years (preschool) 5–12 years (school age)			
If the playground contains equipment for both user age groups, is there a distance separating the two areas?			yes no			
Will signs be posted indicating the appropriate age of the users?			yes no			
Is the playground fenced and separated from traffic?			yes no			
Are the barriers and landscaping designed so they will allow observation of the users by supervisors?			yes no			

Is the sight level and well-drained?	yes 🗌 no					
Is there a septic system located on the school grounds?						
(If yes, the playground should not be located over the	yes 🗌 no					
drainfield. Please show drainfield location on playground	, so <u> </u>					
footprint plan.)						
Equipment Design Information						
If installing fulcrum seesaws, will there be padding under the	ats to help					
prevent arms and legs from being crushed between the seat a	d the ground?					
What is the seesaw height (distance between the maximum a and the ground)?	ainable height inches					
Slide bed exit region length (portion parallel to ground)	inches					
Does the slide layout meet the minimum ASTM/CPSC slide exi on height of the slide?	use zone based yes no					
Installed Equipment Heights						
To-and-fro Swings (distance from ground to pivot point):	inches					
Tire swings (distance from seat to pivot point):	inches					
Upper body equipment (maximum height of equipment):	inches					
Spring toys (height of seat or highest designated play surface)	inches					
Balance beams:	inches					
Track rides (handle height above ground):	inches					
Equipment not recommended for pre-school children (2–5 years old)						
	g spiral slides (more than one turn ~ 360°)					
Free standing arch climbers O	Overhead rings					
	allel bars					
, , , ,	Track rides					
	Vertical sliding poles					
Swinging gates						
Equipment not recommended for public playgrounds						
	Rope swings					
	Swinging dual exercise rings and trapeze bars					
	Swinging gates					
Multiple occupancy swings Tr	mpolines					
Equipment layout (refer to CPSC Section 2.2, pages 5-8 for guidance when planning the layout and						

Equipment layout (refer to CPSC Section 2.2, pages 5-8 for guidance when planning the layout and design of playgrounds. Consider these recommendations when designing the layout)

- Locate ADA transfer stations near school entrances to minimize travel distance.
- Add extra circulation zones to the minimum required use zones to reduce congestion.
- Locate active, physical activities in a separate area from more passive or quiet activities. Popular, heavy use equipment should be dispersed to avoid crowding in any one area.
- Locate composite structures such that the play and traffic patterns around adjacent components are complementary.
- Locate slide exits and moving equipment such as swings and merry-go-rounds at the edge or corners of the playground.
- Guy wires, power lines, and tree limbs should be at least 7 feet above the playground surface.



Submittal Process and Fees

After preliminary review of the submittal, SH&S will notify you if additional submittal materials are necessary. *Final Health District approval is required before construction begins on the project.*

It is your responsibility to contact our office at least five working days prior to completion of the project to schedule a pre-occupancy inspection.

Plan review and preoccupancy inspection fees are charged at our standard hourly rate. If construction begins prior to Health District approval, fees will be calculated at the rate of 1.5 times the usual fee.

I have reviewed and understand the	above information.	
Signature	Date	